



## SECTION I: PRODUCT INFORMATION

PRODUCT: **SikaGrout® 212 SR**REVISION DATE: February 1<sup>st</sup>, 2015

USAGE: NON-SHRINK, CEMENTITIOUS GROUT

MANUFACTURER/SUPPLIER: SIKA CANADA INC.  
601, avenue Delmar  
Pointe Claire, QC  
H9R 4A9

EMERGENCY TELEPHONE NUMBER: **CANUTEC (collect) (613) 996-6666**

TDG CLASSIFICATION: Not Regulated  
UN NUMBER: Not Established  
Packaging Group: Not Applicable

WHMIS Classification: D2A, E  
Class: Not Applicable

## SECTION II: HAZARDOUS INGREDIENTS

Hazardous ingredients	%	T.L.V.	# CAS	LD <sub>50</sub> (mg/kg) (species, route)	LC <sub>50</sub> (species, route)
SILICA SAND	40-70	ACGIH *0.025 mg/m <sup>3</sup>	14808-60-7	Not Available	Not Available
PORTLAND CEMENT	30-60	** 10mg/m <sup>3</sup>	65997-15-1	Not Available	Not Available
* Total	dust				
** Breathable	dust				

## SECTION III: PHYSICAL CHARACTERISTICS

Physical: Powder  
Appearance and Odor: Grey powder, No odor  
Odor Threshold: Not Applicable  
Evaporation Rate: Not Applicable  
Vapor Density: Not Applicable  
Vapor Pressure: Not Applicable

Boiling Point: Not Applicable  
Freezing Point: Not Applicable  
Density: 2.8 g/ml  
Water Solubility: < 1 %  
pH: Not Established  
% volatility: 0  
Water/Oil Distribution: Not Established



PRODUCT: SikaGrout® 212 SR

SECTION IV: FIRE AND EXPLOSION HAZARDS

Flammability: If Yes, under what conditions:	No	TDG Flammability Class:	Not Applicable
		Flammable upper limits (% vol.):	Not Applicable
		Flammable lower limits (% vol.):	Not Applicable
Extinguishing methods:	Not Applicable	Flash Point (method used):	Not Applicable
		Auto-ignition temperature:	Not Applicable
		Dangerous Combustion Products:	Not Applicable
Special Methods:	None	Protect from mechanical impact:	No
		Protect from static discharge:	No

SECTION V: REACTIVITY

Chemical stability: If not, under what conditions:	Yes	Dangerous decomposition products:	Calcium hydroxide at water contact.
Incompatibility with other material: If Yes, which ones:	Yes Water	Polymerization Risks:	No



PRODUCT: SikaGrout® 212 SR

SECTION VI: TOXIC PROPERTIES

ROUTE OF ENTRY / CONTACT

Eyes: May cause irritation, burns, damages to the eyes, may cause cornea inflammation.

Skin: May cause irritation, burns and allergic reactions. The cement can burn the skin without great heat sensation.

Inhalation: May cause irritation to the respiratory system, inflammation to the nose tissues. A regular exposure to the quartz silica may cause changes to the lungs' fibers and lead to silicosis.

Ingestion: May cause an irritation to the throat.

Carcinogenicity: NTP: no, OSHA: no, IARC: yes. According to the IARC the quartz silica is a probable cause of cancer.

Toxic effects on reproduction: Not established

Teratogenicity: Not established

Mutagenicity: Not established

Product with synergistic effects: Unknown

An acute or chronic exposure will increase the toxic effects mentioned in this section and may aggravate respiratory problems.



PRODUCT: SikaGrout® 212 SR

SECTION VII: PREVENTIVE MEASURES

PERSONAL PROTECTIVE EQUIPMENT

Gloves: Ordinary; avoid direct skin contact with the cement.

Respiratory equipment: NIOSH approved mask for when the permissible limit might be exceeded

Eyes: Safety glasses

Shoes: Ordinary

Clothing: Ordinary

Other: No

OTHERS

Ventilation: Sufficient ventilation required to control the quantity of dust.

Procedure in case of leaks: Try to recycle the product if not contaminated. Protect yourself from the dust. Pick-up the spill with vacuum in order to reduce dust inhalation.

Handling and Equipment Methods: Avoid dust contact.

Warehouse Requirements: Keep all containers closed in a cool, dry area.

Special Shipping Instructions: Protect from humidity.

Waste Disposal: Harden with water, then dispose like domestic garbage.



PRODUCT: SikaGrout® 212 SR

## SECTION VIII: FIRST AID

**Skin:** Clean with plenty of soap and water.  
Consult a physician if irritation persists.

**Eyes:** Rinse eyes immediately with plenty of water keeping the eyelids open in order to ensure a complete rinsing.  
This should last at least 15 minutes for maximum protection.  
Consult a physician immediately.

**Inhalation:** In the case of overexposure, evacuate to fresh air.  
Consult a physician if required.

**Ingestion:** Drink plenty of water. Do not induce vomiting.  
Do not give anything by mouth to an unconscious person.  
See a physician immediately.

## SECTION IX: PREPARATION INFORMATION

Prepared By: R & D of Sika Canada Inc.  
Telephone #: (514) 697-2610  
Fax #: (514) 694-2792

**Notice To Reader**

*The information contained in this Material Safety Data Sheet applies only to the actual Sika Canada product identified and described herein. This information is not intended to address, nor does it address the use or application of the identified Sika product in combination with any other material, product or process. All of the information set forth herein is based on technical data regarding the identified product that Sika believes to be reliable as of the date hereof. Prior to each use of any Sika product, the user must always read and follow the warnings and instructions on the product's current Product Data Sheet, product label and Material Safety Data Sheet for each Sika product, which are available at web site and/or telephone number listed in Section IX of this MSDS.*

**SIKA MAKES NO WARRANTIES EXPRESS OR IMPLIED AND ASSUMES NO LIABILITY ARISING FROM THIS INFORMATION OR ITS USE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES AND SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.**

*All sales of Sika products are subject to its current terms and conditions of sale available at [www.sika.ca](http://www.sika.ca) or 514-697-2610.*