

SECTION 1

PRODUCT IDENTIFIER 94310 GLID-U INT ALK UC WHITE
 DATE OF PREPARATION SEPTEMBER 8, 2007
 PRODUCT USE PROTECTIVE COATING
 MANUFACTURED BY: ICI PAINTS NORTH AMERICA, 15885 WEST SPRAGUE ROAD,
 STRONGSVILLE, OHIO 44136, U.S.A
 ICI PAINTS (CANADA), 8200 KEELE STREET,
 CONCORD, ONTARIO L4K 2A5, CANADA.
 EMERGENCY AND MSDS TELEPHONE NUMBER:
 1-800-545-2643
 MSDS PREPARED BY: PRODUCT SAFETY AND TOXICOLOGY DEPARTMENT
 ICI PAINTS NORTH AMERICA

SECTION 2: COMPOSITION/INFORMATION ON INGREDIENTS

INGREDIENT	WT. %:
CHEMICAL NAME LONG OIL ALKYD RESIN	10-20
COMMON NAME : LONG OIL ALKYD RESIN	
CAS NUMBER: CONFIDENTIAL	
CHEMICAL NAME LIMESTONE	20-30
COMMON NAME : LIMESTONE	
CAS NUMBER: 1317-65-3	
CHEMICAL NAME TITANIUM OXIDE	10-20
COMMON NAME : TITANIUM DIOXIDE	
CAS NUMBER: 13463-67-7	
CHEMICAL NAME TREMOLITE, NONASBESTIFORM	.1-1.0
COMMON NAME : TREMOLITE	
CAS NUMBER: 14567-73-8	
CHEMICAL NAME TALC	10-20
COMMON NAME : TALC	
CAS NUMBER: 14807-96-6	
CHEMICAL NAME QUARTZ	.1-1.0
COMMON NAME : QUARTZ	
CAS NUMBER: 14808-60-7	
CHEMICAL NAME DOLOMITE	1-5
COMMON NAME : DOLOMITE	
CAS NUMBER: 16389-88-1	
CHEMICAL NAME MAGNESIUM CARBONATE	1-5
COMMON NAME : MAGNESIUM CARBONATE	
CAS NUMBER: 546-93-0	
CHEMICAL NAME ETHANOL	.1-1.0
COMMON NAME : ETHYL ALCOHOL	
CAS NUMBER: 64-17-5	
CHEMICAL NAME NAPHTHA (PETROLEUM), HEAVY ALKYLATE	10-20
COMMON NAME : HEAVY SOLVENT NAPHTHA	
CAS NUMBER: 64741-65-7	
CHEMICAL NAME WATER	10-20
COMMON NAME : WATER	
CAS NUMBER: 7732-18-5	
CHEMICAL NAME STODDARD SOLVENT	5-10
COMMON NAME : MINERAL SPIRITS	
CAS NUMBER: 8052-41-3	

SECTION 3: HAZARDS IDENTIFICATION

PRIMARY ROUTE(S) OF EXPOSURE

INHALATION, SKIN CONTACT, EYE CONTACT, INGESTION.

EFFECTS OF OVEREXPOSURE

INHALATION PROLONGED INHALATION MAY LEAD TO FATIGUE, DROWSINESS,
 DIZZINESS AND/OR LIGHTHEADEDNESS, HEADACHE, UNCOORDINATION,
 NAUSEA, VOMITING, COUGHING, CENTRAL NERVOUS SYSTEM
 DEPRESSION, DIFFICULTY OF BREATHING, LIVER DAMAGE, KIDNEY
 DAMAGE, PULMONARY EDEMA, LOSS OF CONSCIOUSNESS.

SKIN CONTACT IRRITATION OF SKIN. PROLONGED OR REPEATED CONTACT CAN CAUSE

DERMATITIS, DEFATTING.

EYE CONTACT IRRITATION OF EYES. PROLONGED OR REPEATED CONTACT CAN CAUSE CONJUNCTIVITIS, TEARING OF EYES, REDNESS OF EYES.

INGESTION INGESTION MAY CAUSE LUNG INFLAMMATION AND DAMAGE DUE TO ASPIRATION OF MATERIAL INTO LUNGS, MOUTH AND THROAT IRRITATION, FATIGUE, DIZZINESS AND/OR LIGHTHEADEDNESS, HEADACHE, UNCOORDINATION, NAUSEA, VOMITING, GASTRO-INTESTINAL DISTURBANCES, ABDOMINAL PAIN, CENTRAL NERVOUS SYSTEM DEPRESSION, DIFFICULTY OF BREATHING, CONVULSIONS, LOSS OF CONSCIOUSNESS.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE
EYE, SKIN, RESPIRATORY DISORDERS, KIDNEY DISORDERS.

SECTION 4: FIRST-AID MEASURES

INHALATION REMOVE TO FRESH AIR. RESTORE AND SUPPORT CONTINUED BREATHING.
GET EMERGENCY MEDICAL ATTENTION.
HAVE TRAINED PERSON GIVE OXYGEN IF NECESSARY. GET MEDICAL HELP FOR ANY BREATHING DIFFICULTY.
REMOVE TO FRESH AIR IF INHALATION CAUSES EYE WATERING, HEADACHES, DIZZINESS, OR OTHER DISCOMFORT.

SKIN CONTACT WASH THOROUGHLY WITH SOAP AND WATER. IF ANY PRODUCT REMAINS, GENTLY RUB PETROLEUM JELLY, VEGETABLE OR MINERAL/BABY OIL ONTO SKIN. REPEATED APPLICATIONS MAY BE NEEDED. REMOVE CONTAMINATED CLOTHING.
WASH CONTAMINATED CLOTHING BEFORE RE-USE.

EYE CONTACT FLUSH IMMEDIATELY WITH LARGE AMOUNTS OF WATER, ESPECIALLY UNDER LIDS FOR AT LEAST 15 MINUTES. IF IRRITATION OR OTHER EFFECTS PERSIST, OBTAIN MEDICAL TREATMENT.

INGESTION IF SWALLOWED, OBTAIN MEDICAL TREATMENT IMMEDIATELY.

SECTION 5: FIRE-FIGHTING MEASURES

FLASH POINT (SETA) 102 F./ 39 C. LOWER EXPLOSIVE LIMIT .7 (%)
UPPER EXPLOSIVE LIMIT 13.3 (%)

FIRE EXTINGUISHING MEDIA

DRY CHEMICAL OR FOAM
WATER FOG.
CARBON DIOXIDE.

UNUSUAL FIRE AND EXPLOSION HAZARDS

CLOSED CONTAINERS MAY EXPLODE WHEN EXPOSED TO EXTREME HEAT OR FIRE.
VAPORS ARE HEAVIER THAN AIR AND MAY TRAVEL LONG DISTANCES TO A SOURCE OF IGNITION AND FLASH BACK.
VAPORS CAN FORM EXPLOSIVE MIXTURES IN AIR AT ELEVATED TEMPERATURES.
MAY DECOMPOSE UNDER FIRE CONDITIONS EMITTING IRRITANT AND/OR TOXIC GASES.

FIRE FIGHTING PROCEDURES

WATER MAY BE USED TO COOL AND PROTECT EXPOSED CONTAINERS.
FIREFIGHTERS SHOULD USE FULL PROTECTIVE CLOTHING, EYE PROTECTION, AND SELF-CONTAINED BREATHING APPARATUS.

HAZARDOUS DECOMPOSITION OR COMBUSTION PRODUCTS

CARBON MONOXIDE, CARBON DIOXIDE.
OXIDES OF CALCIUM.

SECTION 6 ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

COMPLY WITH ALL APPLICABLE HEALTH AND ENVIRONMENTAL REGULATIONS.
ELIMINATE ALL SOURCES OF IGNITION. VENTILATE AREA. EVACUATE ALL UNNECESSARY PERSONNEL. PLACE COLLECTED MATERIAL IN PROPER CONTAINER.
COMPLETE PERSONAL PROTECTIVE EQUIPMENT MUST BE USED DURING

CLEANUP.

LARGE SPILLS - SHUT OFF LEAK IF SAFE TO DO SO. DIKE AND CONTAIN SPILL. PUMP TO STORAGE OR SALVAGE VESSELS. USE ABSORBENT TO PICK UP EXCESS RESIDUE. KEEP SALVAGEABLE MATERIAL AND RINSE WATER OUT OF SEWERS AND WATER COURSES. SMALL SPILLS - USE ABSORBENT TO PICK UP RESIDUE AND DISPOSE OF PROPERLY.

SECTION 7 HANDLING AND STORAGE

HANDLING AND STORAGE

STORE BELOW 100F (38C). KEEP AWAY FROM HEAT, SPARKS AND OPEN FLAME. KEEP FROM FREEZING.

OTHER PRECAUTIONS USE ONLY WITH ADEQUATE VENTILATION. DO NOT TAKE INTERNALLY. KEEP OUT OF REACH OF CHILDREN. AVOID CONTACT WITH SKIN AND EYES, AND BREATHING OF VAPORS. WASH HANDS THOROUGHLY AFTER HANDLING, ESPECIALLY BEFORE EATING OR SMOKING. KEEP CONTAINERS TIGHTLY CLOSED AND UPRIGHT WHEN NOT IN USE. EMPTY CONTAINERS MAY CONTAIN HAZARDOUS RESIDUES. GROUND EQUIPMENT WHEN TRANSFERRING TO PREVENT ACCUMULATION OF STATIC CHARGE.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

COMMON NAME :	LIMESTONE		
CAS NUMBER:	1317-65-3		
ACGIH(TWA):	10	MG/M3	OSHA(TWA): 5 MG/M3
COMMON NAME :	TITANIUM DIOXIDE		
CAS NUMBER:	13463-67-7		
ACGIH(TWA):	10	MG/M3	OSHA(TWA): 10 MG/M3
COMMON NAME :	TALC		
CAS NUMBER:	14807-96-6		
ACGIH(TWA):	2	MG/M3	
COMMON NAME :	QUARTZ		
CAS NUMBER:	14808-60-7		
ACGIH(TWA):	.025	MG/M3	OSHA(TWA): 0.1 MG/M3
COMMON NAME :	DOLOMITE		
CAS NUMBER:	16389-88-1		
ACGIH(TWA):	10	MG/M3	OSHA(TWA): 5 MG/M3
COMMON NAME :	MAGNESIUM CARBONATE		
CAS NUMBER:	546-93-0		
			OSHA(TWA): 5 MG/M3
COMMON NAME :	HEAVY SOLVENT NAPHTHA		
CAS NUMBER:	64741-65-7		
ACGIH(TWA):	100	PPM	OSHA(TWA): 500 PPM
COMMON NAME :	MINERAL SPIRITS		
CAS NUMBER:	8052-41-3		
ACGIH(TWA):	100	PPM	OSHA(TWA): 500 PPM

RESPIRATORY PROTECTION

CONTROL ENVIRONMENTAL CONCENTRATIONS BELOW APPLICABLE EXPOSURE STANDARDS WHEN USING THIS MATERIAL. WHEN RESPIRATORY PROTECTION IS DETERMINED TO BE NECESSARY, USE A NIOSH/MSHA (CANADIAN Z94.4) APPROVED ELASTOMERIC SEALING-SURFACE FACEPIECE RESPIRATOR OUTFITTED WITH ORGANIC VAPOR CARTRIDGES AND PAINT SPRAY (DUST/MIST) PREFILTERS. DETERMINE THE PROPER LEVEL OF PROTECTION BY CONDUCTING APPROPRIATE AIR MONITORING. CONSULT 29CFR1910.134 FOR SELECTION OF RESPIRATORS (CANADIAN Z94.4).

VENTILATION

PROVIDE DILUTION VENTILATION OR LOCAL EXHAUST TO PREVENT BUILD-UP OF VAPORS.

USE EXPLOSION-PROOF EQUIPMENT.

PERSONAL PROTECTIVE EQUIPMENT

EYE WASH, SAFETY SHOWER, SAFETY GLASSES OR GOGGLES. IMPERVIOUS GLOVES, IMPERVIOUS CLOTHING.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

VAPOR PRESSURE: NOT AVAILABLE SPECIFIC GRAVITY: 1.468
 BOILING RANGE (F/C): 212-410/100-210 WEIGHT PER GALLON: 12.22/ 14.68IMP
 %VOLATILE BY VOLUME: 55.05
 PHYSICAL STATE: LIQUID APPEARANCE: WHITE
 SOLUBILITY IN WATER: NOT AVAILABLE PH: NOT AVAILABLE

SECTION 10: STABILITY AND REACTIVITY

UNDER NORMAL CONDITIONS

STABLE

SEE SECTION 5 FIRE FIGHTING MEASURES

MATERIALS TO AVOID

OXIDIZERS, ACIDS, BASES, HALOGENS, AMMONIUM SALTS, METALS,
 COMBUSTIBLE MATERIALS.

CONDITIONS TO AVOID

ELEVATED TEMPERATURES, CONTACT WITH OXIDIZING AGENT,
 FREEZING, SPARKS, OPEN FLAME, IGNITION SOURCES.

HAZARDOUS POLYMERIZATION

WILL NOT OCCUR

SECTION 11: TOXICOLOGICAL INFORMATION

COMMON NAME : LIMESTONE
 CAS NUMBER: 1317-65-3
 CARCINOGENICITY LISTED BY: NTP NO IARC NO OSHA NO ACGIH NO
 LD50: 6450.00 MG/KG ORL RAT

COMMON NAME : TITANIUM DIOXIDE
 CAS NUMBER: 13463-67-7
 CARCINOGENICITY LISTED BY: NTP YES 2B IARC YES 2B OSHA NO ACGIH NO
 LD50: 24.00 GM/KG ORL RAT
 LC50: 6820.00 MG/M3/4HR IHL RAT

COMMON NAME : TREMOLITE
 CAS NUMBER: 14567-73-8
 CARCINOGENICITY LISTED BY: NTP NO IARC NO OSHA NO ACGIH NO

COMMON NAME : TALC
 CAS NUMBER: 14807-96-6
 CARCINOGENICITY LISTED BY: NTP NO IARC NO OSHA NO ACGIH YES A4

COMMON NAME : QUARTZ
 CAS NUMBER: 14808-60-7
 CARCINOGENICITY LISTED BY: NTP YES IARC YES 1 OSHA NO ACGIH YES A2

COMMON NAME : DOLOMITE
 CAS NUMBER: 16389-88-1
 CARCINOGENICITY LISTED BY: NTP NO IARC NO OSHA NO ACGIH NO

COMMON NAME : MAGNESIUM CARBONATE
 CAS NUMBER: 546-93-0
 CARCINOGENICITY LISTED BY: NTP NO IARC NO OSHA NO ACGIH NO
 LD50: 16.00 MG/KG ITR MOU

COMMON NAME : HEAVY SOLVENT NAPHTHA
 CAS NUMBER: 64741-65-7
 CARCINOGENICITY LISTED BY: NTP NO IARC NO OSHA NO ACGIH NO

COMMON NAME : MINERAL SPIRITS
 CAS NUMBER: 8052-41-3
 CARCINOGENICITY LISTED BY: NTP NO IARC NO OSHA NO ACGIH NO
 LD50:> 3.00 GM/KG SKN RBT
 LD50:> 5.00 GM/KG ORL RAT

SUPPLEMENTAL HEALTH INFORMATION

NOTICE - REPORTS HAVE ASSOCIATED REPEATED AND PROLONGED
 OCCUPATIONAL OVEREXPOSURE TO SOLVENTS WITH PERMANENT BRAIN
 AND NERVOUS SYSTEM DAMAGE. INTENTIONAL MISUSE BY
 DELIBERATELY CONCENTRATING AND INHALING THE CONTENTS
 MAY BE HARMFUL OR FATAL.

CARCINOGENICITY INHALATION OF NON-ASBESTIFORM COSMETIC GRADE TALC FOR
 2 YEARS AT 6 AND 18 MG/M3 PRODUCED CLEAR EVIDENCE OF

CARCINOGENICITY IN FEMALE RATS (LUNG AND ADRENAL TUMORS) AND SOME EVIDENCE OF CARCINOGENICITY IN MALE RATS (ADRENAL TUMORS). NO EVIDENCE OF CARCINOGENICITY WAS DEMONSTRATED IN MALE AND FEMALE MICE EXPOSED UNDER THE SAME CONDITIONS. MICROSCOPIC EXAMINATION OF THE LUNGS OF RATS AND MICE EXPOSED TO TALC REVEALED ADDITIONAL EXPOSURE RELATED EFFECTS PRIMARILY ASSOCIATED WITH THE INFLAMMATORY RESPONSE. CONTAINS CRYSTALLINE SILICA WHICH IS CONSIDERED A HAZARD BY INHALATION. IARC HAS CLASSIFIED CRYSTALLINE SILICA AS CARCINOGENIC TO HUMANS (GROUP 1). CRYSTALLINE SILICA IS ALSO A KNOWN CAUSE OF SILICOSIS, A NONCANCEROUS LUNG DISEASE. THE NATIONAL TOXICOLOGY PROGRAM (NTP) HAS CLASSIFIED CRYSTALLINE SILICA AS A KNOWN HUMAN CARCINOGEN. IN A LIFETIME INHALATION STUDY, EXPOSURE TO 250 MG/M3 TITANIUM DIOXIDE RESULTED IN THE DEVELOPMENT OF LUNG TUMORS IN RATS. THESE TUMORS OCCURRED ONLY AT DUST LEVELS THAT OVERWHELMED THE ANIMALS' LUNG CLEARANCE MECHANISMS AND WERE DIFFERENT FROM COMMON HUMAN LUNG TUMORS IN BOTH TYPE AND LOCATION. THE RELEVANCE OF THESE FINDINGS TO HUMANS IS UNKNOWN BUT QUESTIONABLE. THE INTERNATIONAL AGENCY FOR RESEARCH ON CANCER (IARC) HAS CLASSIFIED TITANIUM DIOXIDE AS POSSIBLY CARCINOGENIC TO HUMANS (GROUP 2B) BASED ON INADEQUATE EVIDENCE OF CARCINOGENICITY IN HUMANS AND SUFFICIENT EVIDENCE OF CARCINOGENICITY IN EXPERIMENTAL ANIMALS.

REPRODUCTIVE EFFECTS

NO REPRODUCTIVE EFFECTS ARE ANTICIPATED

MUTAGENICITY

NO MUTAGENIC EFFECTS ARE ANTICIPATED

TERATOGENICITY

NO TERATOGENIC EFFECTS ARE ANTICIPATED

SECTION 12: ECOLOGICAL INFORMATION

NO ECOLOGICAL TESTING HAS BEEN DONE BY ICI PAINTS ON THIS PRODUCT AS A WHOLE.

SECTION 13: DISPOSAL CONSIDERATIONS

WASTE DISPOSAL DISPOSE IN ACCORDANCE WITH ALL APPLICABLE REGULATIONS.

SECTION 14: TRANSPORT INFORMATION

DOT	PAINT
IMDG	NOT AVAILABLE
IATA	NOT AVAILABLE
TDG	NOT AVAILABLE

SECTION 15: REGULATORY INFORMATION

SARA SARA CERCLA HAZ AIR MARINE
302 313 302.4 POLLUTANT POLINT

THIS PRODUCT CONTAINS NO SARA 302, CERCLA 302.4 OR HAZARDOUS AIR POLLUTANT CHEMICALS. IT ALSO CONTAINS NO CHEMICALS WHICH ARE SUBJECT TO THE REPORTING REQUIREMENTS UNDER SARA 313.

AS OF THE DATE OF THIS MSDS, ALL OF THE COMPONENTS IN THIS PRODUCT ARE LISTED (OR ARE OTHERWISE EXEMPT FROM LISTING) ON THE TSCA INVENTORY.

THIS PRODUCT HAS BEEN CLASSIFIED IN ACCORDANCE WITH THE HAZARD CRITERIA OF THE CPR (CONTROLLED PRODUCTS REGULATIONS) AND THE MSDS CONTAINS ALL THE INFORMATION REQUIRED BY THE CPR.

SECTION 16: OTHER INFORMATION

THE INFORMATION CONTAINED HEREIN IS BASED ON DATA AVAILABLE AT THE TIME OF PREPARATION OF THIS DATA SHEET AND WHICH ICI PAINTS BELIEVES TO BE RELIABLE. HOWEVER, NO WARRANTY IS EXPRESSED OR IMPLIED REGARDING THE ACCURACY OF THIS DATA.

94310 GLID-U INT ALK UC WHITE

ICI PAINTS SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS INFORMATION, OR OF ANY PRODUCT, METHOD OR APPARATUS MENTIONED AND YOU MUST MAKE YOUR OWN DETERMINATION OF ITS SUITABILITY AND COMPLETENESS FOR YOUR OWN USE, FOR THE PROTECTION OF THE ENVIRONMENT, AND THE HEALTH AND SAFETY OF YOUR EMPLOYEES AND USERS OF THIS MATERIAL.
COMPLIES WITH OSHA HAZARD COMMUNICATION STANDARD
29CFR1910.1200.