

## HAZARDS IDENTIFICATION

(ANSI Section 3)

**Primary route(s) of exposure :** Inhalation, skin contact, eye contact, ingestion.

**Effects of overexposure :**

**Inhalation :** Irritation of respiratory tract. Prolonged inhalation may lead to mucous membrane irritation, fatigue, drowsiness, dizziness and/or lightheadedness, headache, uncoordination, nausea, vomiting, chest pain, blurred vision, coughing, difficulty with speech, central nervous system depression, intoxication, tightness of chest, anesthetic effect or narcosis, difficulty of breathing, bronchitis, tremors, liver damage, kidney damage, loss of consciousness, respiratory failure, asphyxiation, death.

**Skin contact :** Irritation of skin. Prolonged or repeated contact can cause dermatitis, defatting, blistering. Skin contact may result in dermal absorption of component(s) of this product which may cause dizziness and/or lightheadedness, headache, nausea, vomiting, central nervous system depression.

**Eye contact :** Irritation of eyes. Prolonged or repeated contact can cause conjunctivitis, blurred vision, tearing of eyes, redness of eyes, severe eye irritation.

**Ingestion :** Ingestion may cause lung inflammation and damage due to aspiration of material into lungs, mucous membrane irritation, headache, nausea, vomiting, diarrhea, gastro-intestinal disturbances, abdominal pain, central nervous system depression, intoxication, liver damage, kidney damage, pulmonary edema.

**Medical conditions aggravated by exposure :** Eye, skin, respiratory disorders, kidney disorders, liver disorders.

## FIRST-AID MEASURES

(ANSI Section 4)

**Inhalation :** Remove to fresh air. Restore and support continued breathing. Get emergency medical attention. Have trained person give oxygen if necessary. Get medical help for any breathing difficulty. Remove to fresh air if inhalation causes eye watering, headaches, dizziness, or other discomfort.

**Skin contact :** Wash thoroughly with soap and water. If any product remains, gently rub petroleum jelly, vegetable or mineral/baby oil onto skin. Repeated applications may be needed. Remove contaminated clothing. Wash contaminated clothing before re-use. If irritation occurs, consult a physician.

**Eye contact :** Flush immediately with large amounts of water, especially under lids for at least 15 minutes. If irritation or other effects persist, obtain medical treatment.

**Ingestion :** If swallowed, obtain medical treatment immediately.

## FIRE-FIGHTING MEASURES

(ANSI Section 5)

**Fire extinguishing media :** Dry chemical or foam water fog. Carbon dioxide. Closed containers may explode when exposed to extreme heat or fire. Vapors may ignite explosively at ambient temperatures. Vapors are heavier than air and may travel long distances to a source of ignition and flash back. Vapors can form explosive mixtures in air at elevated temperatures. Dust explosion hazard. May decompose under fire conditions emitting irritant and/or toxic gases.

**Fire fighting procedures :** Water may be used to cool and protect exposed containers. Firefighters should use full protective clothing, eye protection, and self-contained breathing apparatus.

**Hazardous decomposition or combustion products :** Carbon monoxide, carbon dioxide, oxides of phosphorus, toxic gases. Oxides of calcium.

## ACCIDENTAL RELEASE MEASURES

(ANSI Section 6)

**Steps to be taken in case material is released or spilled :** Comply with all applicable health and environmental regulations. Eliminate all sources of ignition. Ventilate area. Ventilate area with

explosion-proof equipment. Spills may be collected with absorbent materials. Use non-sparking tools. Evacuate all unnecessary personnel. Place collected material in proper container. Prevent airborne particulates from forming. Complete personal protective equipment must be used during cleanup. Sweep up material. Large spills - shut off leak if safe to do so. Dike and contain spill. Pump to storage or salvage vessels. Use absorbent to pick up excess residue. Keep salvageable material and rinse water out of sewers and water courses. Small spills - use absorbent to pick up residue and dispose of properly.

## HANDLING AND STORAGE

(ANSI Section 7)

**Handling and storage :** Store below 80f. Keep away from heat, sparks and open flame.

**Other precautions :** Use only with adequate ventilation. Do not take internally. Keep out of reach of children. Avoid contact with skin and eyes, and breathing of vapors. Wash hands thoroughly after handling, especially before eating or smoking. Keep containers tightly closed and upright when not in use. Empty containers may contain hazardous residues. Ground equipment when transferring to prevent accumulation of static charge.

## EXPOSURE CONTROLS/PERSONAL PROTECTION

(ANSI Section 8)

**Respiratory protection :** Control environmental concentrations below applicable exposure standards when using this material. When respiratory protection is determined to be necessary, use a NIOSH/MSHA (Canadian z94.4) Approved elastomeric sealing- surface facepiece respirator outfitted with organic vapor cartridges and paint spray (dust/mist) prefilters. Determine the proper level of protection by conducting appropriate air monitoring. Consult 29CFR1910.134 For selection of respirators (Canadian z94.4).

**Ventilation :** Provide dilution ventilation or local exhaust to prevent build-up of vapors. Use explosion-proof equipment. Use non-sparking equipment.

**Personal protective equipment :** Eye wash, safety shower, safety glasses or goggles. Impervious gloves, impervious clothing, apron, boots.

## STABILITY AND REACTIVITY

(ANSI Section 10)

**Under normal conditions :** Stable see section 5 fire fighting measures

**Materials to avoid :** Oxidizers, acids, reducing agents, bases, amines, aluminum, ammonium salts, nitric acid, magnesium, mineral acids.

**Conditions to avoid :** Elevated temperatures, contact with oxidizing agent, high concentration of dust, sparks, open flame, ignition sources.

**Hazardous polymerization :** Will not occur

## TOXICOLOGICAL INFORMATION

(ANSI Section 11)

**Supplemental health information :** Contains a chemical that is moderately toxic by ingestion.

Contains a chemical that may be absorbed through skin. Excessive inhalation of fumes may lead to metal fume fever characterized by a metallic taste in mouth, excessive thirst, coughing, weakness, fatigue, muscular pain, nausea, chills and fever. Notice - reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. Nuisance dust hazard - overexposure may cause mechanical irritation of eyes, skin, and respiratory tract. Contains iron oxide, repeated or prolonged exposure to iron oxide dust may cause siderosis, a benign pneumoconiosis. Other effects of overexposure may include toxicity to liver, kidney, central nervous system, blood.

**Carcinogenicity :** Contains formaldehyde, a potential cancer hazard. Rats exposed to formaldehyde via inhalation developed cancer of the nasal cavity. Evidence in humans is limited (nasal and nasopharyngeal cancer). Formaldehyde is listed as a carcinogen by OSHA, probable human carcinogen (group 2a) by IARC, and a known human carcinogen by NTP. Overexposure can cause eye, skin, and respiratory tract irritation, and skin and respiratory sensitization. Contains crystalline silica which is considered a hazard by inhalation. IARC has classified crystalline silica as carcinogenic to humans (group 1). Crystalline silica is also a known cause of silicosis, a noncancerous lung disease. The national toxicology program (NTP) has classified crystalline silica as a known human carcinogen. The international agency for research on cancer (IARC) has classified carbon black as possibly carcinogenic to humans (group 2b) based on sufficient evidence in animals and inadequate evidence in humans. The international agency for research on cancer (IARC) has evaluated ethylbenzene and classified it as a possible human carcinogen (group 2b) based on sufficient evidence for carcinogenicity in experimental animals, but inadequate evidence for cancer in exposed humans. In a 2 year inhalation study conducted by the national toxicology program (NTP), ethylbenzene vapor at 750 ppm produced kidney and testicular tumors in rats and lung and liver tumors in mice. Genetic toxicity studies showed no genotoxic effects. The relevance of these results to humans is not known. In a lifetime inhalation study, exposure to 250 mg/m3 titanium dioxide resulted in the development of lung tumors in rats. These tumors occurred only at dust levels that overwhelmed the animals' lung clearance mechanisms and were different from common human lung tumors in both type and location. The relevance of these findings to humans is unknown but questionable. The international agency for research on cancer (IARC) has classified titanium dioxide as possibly carcinogenic to humans (group 2b) based on inadequate evidence of carcinogenicity in humans and sufficient evidence of carcinogenicity in experimental animals. Contains methyl ethyl ketoxime (meko). In a lifetime, inhalation study, liver carcinomas were observed in rodents exposed to meko. The relevance to humans is unknown.

**Reproductive effects :** High exposures to xylene in some animal studies, often at maternally toxic levels, have affected embryo/fetal development. The significance of this finding to humans is not known.

**Mutagenicity :** No mutagenic effects are anticipated

**Teratogenicity :** No teratogenic effects are anticipated

**ECOLOGICAL INFORMATION (ANSI Section 12)**

No ecological testing has been done by akzo nobel paints llc on this product as a whole.

**DISPOSAL CONSIDERATIONS (ANSI Section 13)**

**Waste disposal :** Dispose in accordance with all applicable regulations. Avoid discharge to natural waters.

**REGULATORY INFORMATION (ANSI Section 15)**

As of the date of this MSDS, all of the components in this product are listed (or are otherwise exempt from listing) on the TSCA inventory. This product has been classified in accordance with the hazard criteria of the CPR (controlled products regulations) and the MSDS contains all the information required by the CPR.

**Physical Data (ANSI Sections 1, 9, and 14)**

Product Code	Description	Wt. / Gal.	VOC gr. / ltr.	% Volatile by Volume	Flash Point	Boiling Range	HMIS	DOT, proper shipping name
4360-1000	devguard 4360 low voc universal primer white	13.34	337.45	39.51	80 f	212-290	*330	UN1263,paint,3,PGIII
4360-7100	devguard 4360 low voc universal primer red	13.52	329.79	38.61	80 f	212-290	*330	UN1263,paint,3,PGIII

**Ingredients Product Codes with % by Weight (ANSI Section 2)**

Chemical Name	Common Name	CAS. No.	4360-1000	4360-7100
benzene, ethyl-	ethylbenzene	100-41-4	1-5	1-5
2-pentanone	methyl propyl ketone	107-87-9	1-5	1-5
iron oxide	ferric oxide	1309-37-1		1-5
limestone	limestone	1317-65-3	40-50	40-50
benzene, dimethyl-	xylene	1330-20-7	10-20	10-20
iron oxide	iron oxide	1332-37-2		1-5
carbon black	carbon black	1333-86-4		.1-1.0
titanium oxide	titanium dioxide	13463-67-7	5-10	
calcium metasilicate	wollastonite	13983-17-0	1-5	1-5
quartz	quartz	14808-60-7	.1-1.0	.1-1.0
formaldehyde	formaldehyde	50-00-0	LT .01	LT .01
phosphoric acid, zinc salt	zinc phosphate	7779-90-0	1-5	1-5
alkyd resin	alkyd resin	Sup. Conf.	10-20	10-20
phenolic resin	phenolic resin	Sup. Conf.	1-5	1-5

**Chemical Hazard Data**

(ANSI Sections 2, 8, 11, and 15)

Common Name	CAS. No.	ACGIH-TLV				OSHA-PEL				S.R. Std.	S2	S3	CC	H	M	N	I	O
		8-Hour TWA	STEL	C	S	8-Hour TWA	STEL	C	S									
ethylbenzene	100-41-4	100 ppm	125 ppm	not est.	not est.	100 ppm	not est.	not est.	not est.	not est.	n	y	y	y	n	n	y	n
methyl propyl ketone	107-87-9	not est.	150 ppm	not est.	not est.	200 ppm	not est.	not est.	not est.	not est.	n	n	n	n	n	n	n	n
ferric oxide	1309-37-1	5 mg/m3	not est.	not est.	not est.	5 mg/m3	not est.	not est.	not est.	not est.	n	n	n	n	n	n	n	n
limestone	1317-65-3	10 mg/m3	not est.	not est.	not est.	5 mg/m3	not est.	not est.	not est.	not est.	n	n	n	n	n	n	n	n
xylene	1330-20-7	100 ppm	150 ppm	not est.	not est.	100 ppm	not est.	not est.	not est.	not est.	n	y	y	y	n	n	n	n
iron oxide	1332-37-2	5 mg/m3	not est.	not est.	not est.	10 mg/m3	not est.	not est.	not est.	not est.	n	n	n	n	n	n	n	n
carbon black	1333-86-4	3.5 mg/m3	not est.	not est.	not est.	3.5 mg/m3	not est.	not est.	not est.	not est.	n	n	n	n	n	n	y	n
titanium dioxide	13463-67-7	10 mg/m3	not est.	not est.	not est.	10 mg/m3	not est.	not est.	not est.	not est.	n	n	n	n	n	n	y	y
wollastonite	13983-17-0	10 mg/m3	not est.	not est.	not est.	5 mg/m3	not est.	not est.	not est.	not est.	n	n	n	n	n	n	n	n
quartz	14808-60-7	.025 mg/m3	not est.	not est.	not est.	0.1 mg/m3	not est.	not est.	not est.	not est.	n	n	n	n	n	n	y	y
formaldehyde	50-00-0	not est.	not est.	0.3 ppm	not est.	0.75 ppm	2 ppm	not est.	not est.	not est.	y	y	y	y	n	y	y	y
zinc phosphate	7779-90-0	10 mg/m3	not est.	not est.	not est.	15 mg/m3	not est.	not est.	not est.	not est.	n	y	n	n	n	n	n	n
phenolic resin	Sup. Conf.	not est.	not est.	not est.	not est.	not est.	not est.	not est.	not est.	not est.	n	n	n	n	n	n	n	n

**Footnotes:**  
C=Ceiling - Concentration that should not be exceeded, even instantaneously.

S=Skin - Additional exposure, over and above airborne exposure, may result from skin absorption.

n/a=not applicable  
not est=not established  
CC=CERCLA Chemical

ppm=parts per million  
mg/m3=milligrams per cubic meter  
Sup Conf=Supplier Confidential

S2=Sara Section 302 EHS  
S3=Sara Section 313 Chemical  
S.R.Std.=Supplier Recommended Standard

H=Hazardous Air Pollutant, M=Marine Pollutant  
P=Pollutant, S=Severe Pollutant  
Carcinogenicity Listed By:  
N=NTP, I=IARC, O=OSHA, y=yes, n=no

