

HAZARDS IDENTIFICATION

(ANSI Section 3)

Primary route(s) of exposure : Inhalation, skin contact, eye contact, ingestion.

Effects of overexposure :

Inhalation : Irritation of respiratory tract. Prolonged inhalation may lead to mucous membrane irritation, fatigue, drowsiness, dizziness and/or lightheadedness, headache, uncoordination, nausea, vomiting, diarrhea, gastro-intestinal disturbances, abdominal pain, chest pain, blurred vision, sore throat, coughing, choking, difficulty with speech, apathy, central nervous system depression, intoxication, tightness of chest, metallic taste, anesthetic effect or narcosis, difficulty of breathing, allergic response, fever and chills, dehydration, tremors, abnormal blood pressure, liver damage, kidney damage, pulmonary edema, convulsions, pneumoconiosis, loss of consciousness, cyanosis, respiratory failure, asphyxiation, death. Possible sensitization to respiratory tract.

Skin contact : Irritation of skin. Prolonged or repeated contact can cause dermatitis, defatting, blistering, allergic response, severe skin irritation, severe skin irritation or burns. Possible sensitization to skin. Skin contact may result in dermal absorption of component(s) of this product which may cause dizziness and/or lightheadedness, headache, uncoordination, nausea, vomiting, diarrhea, central nervous system depression, anesthetic effect or narcosis, convulsions, loss of consciousness.

Eye contact : Irritation of eyes. Prolonged or repeated contact can cause conjunctivitis, blurred vision, tearing of eyes, redness of eyes, severe eye irritation, severe eye irritation or burns, corneal injury.

Ingestion : Ingestion may cause lung inflammation and damage due to aspiration of material into lungs, mouth and throat irritation, mucous membrane irritation, drowsiness, dizziness and/or lightheadedness, headache, uncoordination, nausea, vomiting, diarrhea, gastro-intestinal disturbances, abdominal pain, visual disturbances, apathy, central nervous system depression, intoxication, anesthetic effect or narcosis, difficulty of breathing, burns of the mouth, throat, stomach, liver damage, kidney damage, pulmonary edema, convulsions, loss of consciousness, respiratory failure, death.

Medical conditions aggravated by exposure : Eye, skin, respiratory disorders, lung disorders, asthma-like conditions, kidney disorders, liver disorders, nervous system disorders, allergies.

FIRST-AID MEASURES

(ANSI Section 4)

Inhalation : Remove to fresh air. Restore and support continued breathing. Get emergency medical attention. Have trained person give oxygen if necessary. Get medical help for any breathing difficulty. Remove to fresh air if inhalation causes eye watering, headaches, dizziness, or other discomfort.

Skin contact : Wash thoroughly with soap and water. If any product remains, gently rub petroleum jelly, vegetable or mineral/baby oil onto skin. Repeated applications may be needed. Remove contaminated clothing. Wash contaminated clothing before re-use. Dispose of contaminated leather items, such as shoes and belts. If irritation occurs, consult a physician.

Eye contact : Flush immediately with large amounts of water, especially under lids for at least 15 minutes. If irritation or other effects persist, obtain medical treatment.

Ingestion : If swallowed, obtain medical treatment immediately.

FIRE-FIGHTING MEASURES

(ANSI Section 5)

Fire extinguishing media : Dry chemical or foam water fog. Carbon dioxide. Closed containers may explode when exposed to extreme heat or fire. Vapors may ignite explosively at ambient temperatures. Vapors are heavier than air and may travel long distances to a source of ignition and flash back. Vapors can form explosive mixtures in air at elevated temperatures. Closed containers may burst if exposed to extreme heat or fire. Dust explosion hazard. Solvent must not be allowed to

evaporate because contact of water with aluminum dust generates hydrogen, which is a flammable gas. May decompose under fire conditions emitting irritant and/or toxic gases.

Fire fighting procedures : Water may be used to cool and protect exposed containers. Firefighters should use full protective clothing, eye protection, and self-contained breathing apparatus. Self-contained breathing apparatus recommended.

Hazardous decomposition or combustion products : Carbon monoxide, carbon dioxide, oxides of nitrogen, acrid fumes, oxides of sulfur, aldehydes, aluminum oxide, toxic gases, barium compounds, smoke and soot. Phenolics, cyanides, smoke.

ACCIDENTAL RELEASE MEASURES

(ANSI Section 6)

Steps to be taken in case material is released or spilled : Comply with all applicable health and environmental regulations. Eliminate all sources of ignition. Ventilate area. Spills may be collected with absorbent materials. Use non-sparking tools. Evacuate all unnecessary personnel. Place collected material in proper container. Complete personal protective equipment must be used during cleanup. Large spills - shut off leak if safe to do so. Dike and contain spill. Pump to storage or salvage vessels. Use absorbent to pick up excess residue. Keep salvageable material and rinse water out of sewers and water courses. Small spills - use absorbent to pick up residue and dispose of properly.

HANDLING AND STORAGE

(ANSI Section 7)

Handling and storage : Store below 100F (38C). Store in original containers. Isolated storage is desirable. Keep away from heat, sparks and open flame.

Other precautions : Use only with adequate ventilation. Do not take internally. Keep out of reach of children. Avoid contact with skin and eyes, and breathing of vapors. Wash hands thoroughly after handling, especially before eating or smoking. Keep containers tightly closed and upright when not in use. Avoid conditions which result in formation of inhalable particles such as spraying or abrading (sanding) painted surfaces. If such conditions cannot be avoided, use appropriate respiratory protection as directed under exposure controls/personal protection. Empty containers may contain hazardous residues. Ground equipment when transferring to prevent accumulation of static charge.

EXPOSURE CONTROLS/PERSONAL PROTECTION

(ANSI Section 8)

Respiratory protection : Control environmental concentrations below applicable exposure standards when using this material. When respiratory protection is determined to be necessary, use a NIOSH/MSHA (Canadian z94.4) Approved elastomeric sealing- surface facepiece respirator outfitted with organic vapor cartridges and paint spray (dust/mist) prefilters. Determine the proper level of protection by conducting appropriate air monitoring. Consult 29CFR1910.134 For selection of respirators (Canadian z94.4).

Ventilation : Provide dilution ventilation or local exhaust to prevent build-up of vapors. Use explosion-proof equipment.

Personal protective equipment : Eye wash, safety shower, safety glasses or goggles. Impervious gloves, impervious clothing, face shield, apron.

STABILITY AND REACTIVITY

(ANSI Section 10)

Under normal conditions : Stable see section 5 fire fighting measures

Materials to avoid : Oxidizers, acids, reducing agents, bases, aldehydes, isocyanates, amines, aluminum, nitric acid, halogenated compounds, combustible materials, lewis acids, mineral acids. Nitrates.

Conditions to avoid : Elevated temperatures, contact with oxidizing agent, storage near acids, sparks, open flame, ignition sources.

Hazardous polymerization : Will not occur may polymerize in presence of aliphatic amines.

The information contained herein is based on data available at the time of preparation of this data sheet which Akzo Nobel Paints believes to be reliable. However, no warranty is expressed or implied regarding the accuracy of this data. Akzo Nobel Paints shall not be responsible for the use of this information, or of any product, method or apparatus mentioned and you must make your own determination of its suitability and completeness for your own use, for the protection of the environment, and the health and safety of your employees and the users of this material. Complies with OSHA hazard communication standard 29CFR 1910.1200.

TOXICOLOGICAL INFORMATION**(ANSI Section 11)**

Supplemental health information : Contains a chemical that is moderately toxic by ingestion. Contains a chemical that may be absorbed through skin. Notice - reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. Other effects of overexposure may include toxicity to liver, kidney, lungs, central nervous system, blood.

Carcinogenicity : Inhalation of non-asbestiform cosmetic grade talc for 2 years at 6 and 18 mg/m³ produced clear evidence of carcinogenicity in female rats (lung and adrenal tumors) and some evidence of carcinogenicity in male rats (adrenal tumors). No evidence of carcinogenicity was demonstrated in male and female mice exposed under the same conditions. Microscopic examination of the lungs of rats and mice exposed to talc revealed additional exposure related effects primarily associated with the inflammatory response. In long term (2 year) inhalation studies, the national toxicology program (NTP) found clear evidence of carcinogenic activity in mice and male rats and some evidence of carcinogenic activity in female rats exposed to cumene. Contains crystalline silica which is considered a hazard by inhalation. IARC has classified crystalline silica as carcinogenic to humans (group 1). Crystalline silica is also a known cause of silicosis, a noncancerous lung disease. The national toxicology program (NTP) has classified crystalline silica as a known human carcinogen. The international agency for research on cancer (IARC) has classified carbon black as possibly carcinogenic to humans (group 2b) based on sufficient evidence in animals and inadequate evidence in humans. The international agency for research on cancer (IARC) has evaluated ethylbenzene and classified it as a possible human carcinogen (group 2b) based on sufficient evidence for carcinogenicity in experimental animals, but inadequate evidence for cancer in exposed humans. In a 2 year inhalation study conducted by the national toxicology program (NTP), ethylbenzene vapor at 750 ppm produced kidney and testicular tumors in rats and lung and liver tumors in mice. Genetic toxicity studies showed no genotoxic effects. The relevance of these results to humans is not known. In a lifetime inhalation study, exposure to 250 mg/m³ titanium dioxide resulted in the development of lung tumors in rats. These tumors occurred only at dust levels that overwhelmed the animals' lung clearance mechanisms and were different from common human lung tumors in both type and location. The relevance of these findings to humans is unknown but questionable. The international agency for research on cancer (IARC) has classified titanium dioxide as possibly carcinogenic to humans (group 2b) based on inadequate evidence of carcinogenicity in humans and sufficient evidence of carcinogenicity in experimental animals.

Reproductive effects : High exposures to xylene in some animal studies, often at maternally toxic levels, have affected embryo/fetal development. The significance of this finding to humans is not known.

Mutagenicity : No mutagenic effects are anticipated

Teratogenicity : No teratogenic effects are anticipated

ECOLOGICAL INFORMATION**(ANSI Section 12)**

No ecological testing has been done by akzo nobel paints llc on this product as a whole.

DISPOSAL CONSIDERATIONS**(ANSI Section 13)**

Waste disposal : Dispose in accordance with all applicable regulations. Avoid discharge to natural waters.

REGULATORY INFORMATION**(ANSI Section 15)**

As of the date of this MSDS, all of the components in this product are listed (or are otherwise exempt from listing) on the TSCA inventory. This product contains 10% or greater of a chemical classified by DOT as a marine pollutant (see Chemical Hazard Data table). This product has been classified in accordance with the hazard criteria of the CPR (controlled products regulations) and the MSDS contains all the information required by the CPR.

Physical Data**(ANSI Sections 1, 9, and 14)**

Product Code	Description	Wt. / Gal.	VOC gr. / ltr.	% Volatile by Volume	Flash Point	Boiling Range	HMIS	DOT, proper shipping name
224F2534N	devran 224hs high build epoxy coating med gray bas	12.76	243.51	29.20	100 f	237-355	*220	UN1263, paint, combustible liquid, PGIII
224F2950N	devran 224hs high build gray	13.05	249.62	29.92	100 f	237-355	*220	UN1263, paint, combustible liquid, PGIII
224F3501N	devran 224hs high build epoxy coating white base p	13.03	91.34	31.16	100 f	208-208	*320	UN1263, paint, combustible liquid, PGIII
224F3520N	devran 224hs high build epoxy coating pt-1 white b	13.05	249.74	29.91	100 f	237-355	*220	UN1263, paint, combustible liquid, PGIII
224F9100N	devran 224hs high build epoxy coating, aluminum ba	13.20	236.44	27.46	100 f	237-355	*220	UN1263, paint, combustible liquid, PGIII
224F9400N	devran 224hs epoxy high build safety yellow base	12.20	278.00	32.30	100 f	237-355	*320	UN1263, paint, combustible liquid, PGIII
224F9501N	devran 224hs high build epoxy coating deep tint ba	11.75	266.13	31.92	100 f	237-415	*320	UN1263, paint, combustible liquid, PGIII
224F9502N	devran 224hs high build epoxy coating neutral base	10.86	272.43	32.69	100 f	237-415	*320	UN1263, paint, combustible liquid, PGIII
224F9903N	devran 224hs high build epoxy black base portion	12.82	243.15	29.17	100 f	237-355	*220	UN1263, paint, combustible liquid, PGIII
224G0908	devran 224hs high build epoxy coating, neutral con	11.76	126.16	27.64	100 f	208-349	*320	UN2924, flammable liquid, corrosive, n.o.s.,(resin solution, alkyphenols), 3(8), PGIII

Ingredients**Product Codes with % by Weight (ANSI Section 2)**

Chemical Name	Common Name	CAS. No.	224F2534N	224F2950N	224F3501N	224F3520N	224F9100N	224F9400N	224F9501N	224F9502N	224F9903N	224G0908
benzene, ethyl-	ethylbenzene	100-41-4	.1-1.0	.1-1.0	.1-1.0	.1-1.0	.1-1.0	.1-1.0	.1-1.0	.1-1.0	.1-1.0	.1-1.0
benzenemethanol	benzyl alcohol	100-51-6					1-5	1-5				
2-pentanone, 4-methyl-	methyl isobutyl ketone	108-10-1	1-5	1-5		1-5	1-5	1-5	5-10	5-10	1-5	
1,3,5-trimethylbenzene	1,3,5-trimethylbenzene	108-67-8	.1-1.0	.1-1.0		.1-1.0	.1-1.0	.1-1.0	.1-1.0	1-5	.1-1.0	
1,2,-ethanediamine, n,n'-bis(2-aminoethyl)-	triethylenetetramine	112-24-3										1-5
antigorite	antigorite	12135-86-3	5-10	1-5		1-5	5-10				5-10	
iron oxide magnetite	iron oxide magnetite	12227-89-3									5-10	
benzene, dimethyl-	xylene	1330-20-7	.1-1.0	.1-1.0	.1-1.0	.1-1.0	.1-1.0	.1-1.0	1-5	1-5	.1-1.0	1-5

Ingredients (Continued)

Product Codes with % by Weight (ANSI Section 2)

Chemical Name	Common Name	CAS. No.	224F2534N	224F2950N	224F3501N	224F3520N	224F9100N	224F9400N	224F9501N	224F9502N	224F9903N	224G0908
carbon black	carbon black	1333-86-4	.1-1.0								1-5	
titanium oxide	titanium dioxide	13463-67-7	5-10	20-30	20-30	20-30		1-5	10-20			
calcium metasilicate	wollastonite	13983-17-0			1-5			1-5	1-5	1-5		1-5
tremolite, nonasbestiform	tremolite	14567-73-8	5-10	5-10		5-10	5-10				5-10	
talc	talc	14807-96-6	5-10	1-5	5-10	1-5	5-10	10-20	5-10	10-20	5-10	5-10
quartz	quartz	14808-60-7	10-20	10-20	10-20	10-20		.1-1.0	10-20	10-20	10-20	5-10
oxirane,2,2'-((1-methylethylidene) bis(4,1-phenyleneoxymethylene)) bis-	diglycidyl ether of bisphenol a	1675-54-3				10-20						
anthophyllite, nonasbestiform	anthophyllite	17068-78-9	1-5	.1-1.0		.1-1.0	1-5				1-5	
aluminum hydroxide	aluminum hydroxide	21645-51-2		1-5		1-5						
phenol, 4,4'-(1-methylethylidene)bis-, polymer with 2,2'-((1-methylethylidene)bis(4,1-phenyleneoxymethylene))bis(oxirane)	epoxy resin	25036-25-3				10-20						
oxirane,2,2'-((1-methylethylidene)bis(4,1-phenyleneoxymethylene))bis, homopolymer	epoxy resin	25085-99-8	30-40	30-40	30-40		30-40	30-40	30-40	40-50	30-40	
acetic acid, 1,1-dimethylethyl ester	tert-butyl acetate	540-88-5			10-20							5-10
butanamide, 2-((2-methoxy-4-nitrophenyl)azo) -n-(2-methoxyphenyl)-3-oxo-	pigment yellow 74	6358-31-2						5-10				
solvent naphtha (petroleum), light aromatic	light aromatic solvent naphtha	64742-95-6	1-5	1-5		1-5		1-5	1-5	1-5	1-5	1-5
fatty acids, c18-unsatd., dimers, reaction products with polyethylenepolyamines	polyamide resin	68410-23-1										20-30
1-butanol	n-butanol	71-36-3	1-5	1-5	1-5	1-5	1-5	1-5	1-5	1-5	1-5	
aluminum	aluminum	7429-90-5					5-10					
sulfuric acid, barium salt	barium sulfate	7727-43-7					20-30	10-20				20-30
stoddard solvent	mineral spirits	8052-41-3					1-5					
phenol, 4-nonyl-, branched	4-nonylphenol, branched	84852-15-3										10-20
benzene,1,2,4-trimethyl-	pseudocumene	95-63-6	1-5	1-5		1-5	.1-1.0	1-5	1-5	1-5	1-5	1-5
benzene, (1-methylethyl)-	cumene	98-82-8	.1-1.0	.1-1.0		.1-1.0		.1-1.0	.1-1.0	.1-1.0	.1-1.0	.1-1.0
castor oil derivative	rheological additive	Sup. Conf.							1-5	1-5		

Chemical Hazard Data

(ANSI Sections 2, 8, 11, and 15)

Common Name	CAS. No.	ACGIH-TLV				OSHA-PEL				S.R. Std.	S2	S3	CC	H	M	N	I	O
		8-Hour TWA	STEL	C	S	8-Hour TWA	STEL	C	S									
ethylbenzene	100-41-4	100 ppm	125 ppm	not est.	not est.	100 ppm	not est.	not est.	not est.	not est.	n	y	y	y	n	n	y	n
benzyl alcohol	100-51-6	not est.	not est.	not est.	not est.	not est.	not est.	not est.	not est.	not est.	n	n	n	n	n	n	n	n
methyl isobutyl ketone	108-10-1	20 ppm	75 ppm	not est.	not est.	100 ppm	not est.	not est.	not est.	not est.	n	y	y	y	n	n	n	n
1,3,5-trimethylbenzene	108-67-8	25 ppm	35 ppm	not est.	not est.	not est.	not est.	not est.	not est.	not est.	n	n	n	n	n	n	n	n
triethylenetetramine	112-24-3	not est.	not est.	not est.	not est.	not est.	not est.	not est.	not est.	not est.	n	n	n	n	n	n	n	n
antigorite	12135-86-3	not est.	not est.	not est.	not est.	not est.	not est.	not est.	not est.	not est.	n	n	n	n	n	n	n	n
iron oxide magnetite	12227-89-3	not est.	not est.	not est.	not est.	not est.	not est.	not est.	not est.	not est.	n	n	n	n	n	n	n	n
xylene	1330-20-7	100 ppm	150 ppm	not est.	not est.	100 ppm	not est.	not est.	not est.	not est.	n	y	y	y	n	n	n	n
carbon black	1333-86-4	3.5 mg/m3	not est.	not est.	not est.	3.5 mg/m3	not est.	not est.	not est.	not est.	n	n	n	n	n	n	y	n
titanium dioxide	13463-67-7	10 mg/m3	not est.	not est.	not est.	10 mg/m3	not est.	not est.	not est.	not est.	n	n	n	n	n	y	y	n
wollastonite	13983-17-0	10 mg/m3	not est.	not est.	not est.	5 mg/m3	not est.	not est.	not est.	not est.	n	n	n	n	n	n	n	n
tremolite	14567-73-8	not est.	not est.	not est.	not est.	not est.	not est.	not est.	not est.	not est.	n	n	n	n	n	n	n	n
talc	14807-96-6	2 mg/m3	not est.	not est.	not est.	.1 mg/m3	not est.	not est.	not est.	not est.	n	n	n	n	n	n	n	n
quartz	14808-60-7	.025 mg/m3	not est.	not est.	not est.	0.1 mg/m3	not est.	not est.	not est.	not est.	n	n	n	n	n	y	y	n
diglycidyl ether of bisphenol a	1675-54-3	not est.	not est.	not est.	not est.	not est.	not est.	not est.	not est.	not est.	n	n	n	n	n	n	n	n
anthophyllite	17068-78-9	not est.	not est.	not est.	not est.	not est.	not est.	not est.	not est.	not est.	n	n	n	n	n	n	n	n
aluminum hydroxide	21645-51-2	10 mg/m3	not est.	not est.	not est.	5 mg/m3	not est.	not est.	not est.	not est.	n	n	n	n	n	n	n	n
epoxy resin	25036-25-3	not est.	not est.	not est.	not est.	not est.	not est.	not est.	not est.	not est.	n	n	n	n	n	n	n	n
epoxy resin	25085-99-8	not est.	not est.	not est.	not est.	not est.	not est.	not est.	not est.	not est.	n	n	n	n	n	n	n	n

Footnotes:
C=Ceiling - Concentration that should not be exceeded, even instantaneously.

S=Skin - Additional exposure, over and above airborne exposure, may result from skin absorption.

n/a=not applicable
not est=not established
CC=CERCLA Chemical

ppm=parts per million
mg/m3=milligrams per cubic meter
Sup Conf=Supplier Confidential

S2=Sara Section 302 EHS
S3=Sara Section 313 Chemical
S.R.Std.=Supplier Recommended Standard

H=Hazardous Air Pollutant, M=Marine Pollutant
P=Pollutant, S=Severe Pollutant
Carcinogenicity Listed By:
N=NTP, I=IARC, O=OSHA, y=yes, n=no

Chemical Hazard Data (Continued) (ANSI Sections 2, 8, 11, and 15)

Common Name	CAS. No.	ACGIH-TLV				OSHA-PEL				S.R. Std.	S2	S3	CC	H	M	N	I	O
		8-Hour TWA	STEL	C	S	8-Hour TWA	STEL	C	S									
tert-butyl acetate	540-88-5	200 ppm	not est.	not est.	not est.	200 ppm	not est.	not est.	not est.	not est.	n	n	y	n	n	n	n	n
pigment yellow 74	6358-31-2	not est.	not est.	not est.	not est.	not est.	not est.	not est.	not est.	not est.	n	n	n	n	n	n	n	n
light aromatic solvent naphtha	64742-95-6	not est.	not est.	not est.	not est.	500x ppm	not est.	not est.	not est.	not est.	n	n	n	n	n	n	n	n
polyamide resin	68410-23-1	not est.	not est.	not est.	not est.	not est.	not est.	not est.	not est.	not est.	n	n	n	n	n	n	n	n
n-butanol	71-36-3	20 ppm	not est.	not est.	not est.	100 ppm	not est.	not est.	not est.	not est.	n	y	y	n	n	n	n	n
aluminum	7429-90-5	1 mg/m3	not est.	not est.	not est.	5 mg/m3	not est.	not est.	not est.	not est.	n	y	n	n	n	n	n	n
barium sulfate	7727-43-7	10 mg/m3	not est.	not est.	not est.	5 mg/m3	not est.	not est.	not est.	not est.	n	n	n	n	n	n	n	n
mineral spirits	8052-41-3	100 ppm	not est.	not est.	not est.	500 ppm	not est.	not est.	not est.	not est.	n	n	n	n	n	n	n	n
4-nonylphenol, branched	84852-15-3	not est.	not est.	not est.	not est.	not est.	not est.	not est.	not est.	not est.	n	n	n	n	p	n	n	n
pseudocumene	95-63-6	not est.	not est.	not est.	not est.	not est.	not est.	not est.	not est.	not est.	n	y	n	n	n	n	n	n
cumene	98-82-8	50 ppm	not est.	not est.	not est.	50 ppm	not est.	not est.	y	not est.	n	y	y	y	n	n	n	n
rheological additive	Sup. Conf.	not est.	not est.	not est.	not est.	not est.	not est.	not est.	not est.	not est.	n	n	n	n	n	n	n	n

Footnotes:

C=Ceiling - Concentration that should not be exceeded, even instantaneously.

S=Skin - Additional exposure, over and above airborne exposure, may result from skin absorption.

n/a=not applicable
not est.=not established
CC=CERCLA Chemical

ppm=parts per million
mg/m3=milligrams per cubic meter
Sup Conf=Supplier Confidential

S2=Sara Section 302 EHS
S3=Sara Section 313 Chemical
S.R. Std.=Supplier Recommended Standard

H=Hazardous Air Pollutant, M=Marine Pollutant
P=Pollutant, S=Severe Pollutant
Carcinogenicity Listed By:
N=NTP, I=IARC, O=OSHA, y=yes, n=no

