

SECTION 1

PRODUCT IDENTIFIER 2000.00590 221C0908 DEVTAR 5A CONVERTER
VERT ER

DATE OF PREPARATION SEPTEMBER 8, 2007

PRODUCT USE PROTECTIVE COATING

MANUFACTURED BY: ICI PAINTS NORTH AMERICA, 15885 WEST SPRAGUE ROAD,
STRONGSVILLE, OHIO 44136, U.S.A
ICI PAINTS (CANADA), 8200 KEELE STREET,
CONCORD, ONTARIO L4K 2A5, CANADA.

EMERGENCY AND MSDS TELEPHONE NUMBER:
1-800-545-2643

MSDS PREPARED BY: PRODUCT SAFETY AND TOXICOLOGY DEPARTMENT
ICI PAINTS NORTH AMERICA

SECTION 2: COMPOSITION/INFORMATION ON INGREDIENTS

INGREDIENT	WT. %:
CHEMICAL NAME CASTOR OIL DERIVATIVE	1-5
COMMON NAME : RHEOLOGICAL ADDITIVE	
CAS NUMBER: CONFIDENTIAL	
CHEMICAL NAME BENZENE, ETHYL-	1-5
COMMON NAME : ETHYLBENZENE	
CAS NUMBER: 100-41-4	
CHEMICAL NAME 1,2,-ETHANEDIAMINE, N,N'-BIS(2-AMINOETHYL)-	.1-1.0
COMMON NAME : TRIETHYLENETETRAMINE	
CAS NUMBER: 112-24-3	
CHEMICAL NAME MICA	20-30
COMMON NAME : MICA	
CAS NUMBER: 12001-26-2	
CHEMICAL NAME ANTIGORITE	5-10
COMMON NAME : ANTIGORITE	
CAS NUMBER: 12135-86-3	
CHEMICAL NAME BENZENE, DIMETHYL-	10-20
COMMON NAME : XYLENE	
CAS NUMBER: 1330-20-7	
CHEMICAL NAME TREMOLITE, NONASBESTIFORM	10-20
COMMON NAME : TREMOLITE	
CAS NUMBER: 14567-73-8	
CHEMICAL NAME TALC	5-10
COMMON NAME : TALC	
CAS NUMBER: 14807-96-6	
CHEMICAL NAME ANTHOPHYLLITE, NONASBESTIFORM	1-5
COMMON NAME : ANTHOPHYLLITE	
CAS NUMBER: 17068-78-9	
CHEMICAL NAME FATTY ACIDS, C18-UNSATD., DIMERS, REACTION PRODUCTS WITH POLYETHYLENEPOLYAMINES	10-20
COMMON NAME : POLYAMIDE RESIN	
CAS NUMBER: 68410-23-1	
CHEMICAL NAME 1-BUTANOL	10-20
COMMON NAME : N-BUTANOL	
CAS NUMBER: 71-36-3	
CHEMICAL NAME BENZENESULFONIC ACID, MONO-C15-30-BRANCHED ALKYL AN C11-13-BRANCHED AND LINEAR ALKYL DERIVS., CALCIUM S OVERBASED	1-5
COMMON NAME : CALCIUM ALKYL BENZENESULFONATE	
CAS NUMBER: 71486-79-8	
CHEMICAL NAME BENZENE, 1,2,4-TRIMETHYL-	.1-1.0
COMMON NAME : PSEUDOCUMENE	
CAS NUMBER: 95-63-6	

SECTION 3: HAZARDS IDENTIFICATION

PRIMARY ROUTE(S) OF EXPOSURE
INHALATION, SKIN CONTACT, EYE CONTACT, INGESTION.

2000.00590 221C0908 DEVTAR 5A CONVERTER

EFFECTS OF OVEREXPOSURE

INHALATION	PROLONGED INHALATION MAY LEAD TO MUCOUS MEMBRANE IRRITATION, FATIGUE, DROWSINESS, DIZZINESS AND/OR LIGHTHEADEDNESS, HEADACHE, UNCOORDINATION, NAUSEA, VOMITING, DIARRHEA, ABDOMINAL PAIN, CHEST PAIN, BLURRED VISION, COUGHING, DIFFICULTY WITH SPEECH, APATHY, CENTRAL NERVOUS SYSTEM DEPRESSION, INTOXICATION, TIGHTNESS OF CHEST, METALLIC TASTE, ANESTHETIC EFFECT OR NARCOSIS, DIFFICULTY OF BREATHING, ALLERGIC RESPONSE, FEVER AND CHILLS, DEHYDRATION, TREMORS, LIVER DAMAGE, KIDNEY DAMAGE, LOSS OF CONSCIOUSNESS, RESPIRATORY FAILURE, ASPHYXIATION, DEATH. POSSIBLE SENSITIZATION TO RESPIRATORY TRACT.
SKIN CONTACT	IRRITATION OF SKIN. PROLONGED OR REPEATED CONTACT CAN CAUSE DERMATITIS, DEFATTING, BLISTERING, SEVERE SKIN IRRITATION, SEVERE SKIN IRRITATION OR BURNS.
EYE CONTACT	IRRITATION OF EYES. PROLONGED OR REPEATED CONTACT CAN CAUSE CONJUNCTIVITIS, BLURRED VISION, TEARING OF EYES, REDNESS OF EYES, SEVERE EYE IRRITATION, SEVERE EYE IRRITATION OR BURNS, CORNEAL INJURY.
INGESTION	INGESTION MAY CAUSE LUNG INFLAMMATION AND DAMAGE DUE TO ASPIRATION OF MATERIAL INTO LUNGS, MOUTH AND THROAT IRRITATION, DROWSINESS, DIZZINESS AND/OR LIGHTHEADEDNESS, HEADACHE, UNCOORDINATION, NAUSEA, VOMITING, DIARRHEA, GASTRO-INTESTINAL DISTURBANCES, ABDOMINAL PAIN, VISUAL DISTURBANCES, APATHY, CENTRAL NERVOUS SYSTEM DEPRESSION, ANESTHETIC EFFECT OR NARCOSIS, BURNS OF THE MOUTH, THROAT, STOMACH, LIVER DAMAGE, KIDNEY DAMAGE, PULMONARY EDEMA, LOSS OF CONSCIOUSNESS, RESPIRATORY FAILURE, DEATH.
MEDICAL CONDITIONS	AGGRAVATED BY EXPOSURE EYE, SKIN, RESPIRATORY DISORDERS, KIDNEY DISORDERS, ALLERGIES.

SECTION 4: FIRST-AID MEASURES

INHALATION	REMOVE TO FRESH AIR. RESTORE AND SUPPORT CONTINUED BREATHING. GET EMERGENCY MEDICAL ATTENTION. HAVE TRAINED PERSON GIVE OXYGEN IF NECESSARY. GET MEDICAL HELP FOR ANY BREATHING DIFFICULTY.
SKIN CONTACT	WASH THOROUGHLY WITH SOAP AND WATER. IF ANY PRODUCT REMAINS, GENTLY RUB PETROLEUM JELLY, VEGETABLE OR MINERAL/BABY OIL ONTO SKIN. REPEATED APPLICATIONS MAY BE NEEDED. REMOVE CONTAMINATED CLOTHING. WASH CONTAMINATED CLOTHING BEFORE RE-USE. DISPOSE OF CONTAMINATED LEATHER ITEMS, SUCH AS SHOES AND BELTS. IF IRRITATION OCCURS, CONSULT A PHYSICIAN.
EYE CONTACT	FLUSH IMMEDIATELY WITH LARGE AMOUNTS OF WATER, ESPECIALLY UNDER LIDS FOR AT LEAST 15 MINUTES. IF IRRITATION OR OTHER EFFECTS PERSIST, OBTAIN MEDICAL TREATMENT.
INGESTION	IF SWALLOWED, OBTAIN MEDICAL TREATMENT IMMEDIATELY.

SECTION 5: FIRE-FIGHTING MEASURES

FLASH POINT (SETA)	80 F./ 27 C.	LOWER EXPLOSIVE LIMIT	1.0	(%)
		UPPER EXPLOSIVE LIMIT	7.0	(%)
FIRE EXTINGUISHING MEDIA	DRY CHEMICAL OR FOAM WATER FOG. CARBON DIOXIDE.			
UNUSUAL FIRE AND EXPLOSION HAZARDS	CLOSED CONTAINERS MAY EXPLODE WHEN EXPOSED TO EXTREME HEAT OR FIRE. VAPORS MAY IGNITE EXPLOSIVELY AT AMBIENT TEMPERATURES. VAPORS ARE HEAVIER THAN AIR AND MAY TRAVEL LONG DISTANCES			

2000.00590 221C0908 DEVTAR 5A CONVERTER

TO A SOURCE OF IGNITION AND FLASH BACK.
VAPORS CAN FORM EXPLOSIVE MIXTURES IN AIR AT ELEVATED
TEMPERATURES.
MAY DECOMPOSE UNDER FIRE CONDITIONS EMITTING IRRITANT AND/OR
TOXIC GASES.

FIRE FIGHTING PROCEDURES

WATER MAY BE USED TO COOL AND PROTECT EXPOSED CONTAINERS.
FIREFIGHTERS SHOULD USE FULL PROTECTIVE CLOTHING, EYE
PROTECTION, AND SELF-CONTAINED BREATHING APPARATUS.
SELF-CONTAINED BREATHING APPARATUS RECOMMENDED.

HAZARDOUS DECOMPOSITION OR COMBUSTION PRODUCTS

CARBON MONOXIDE, CARBON DIOXIDE, OXIDES OF NITROGEN,
ALDEHYDES, TOXIC GASES.
CYANIDES.

SECTION 6 ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

COMPLY WITH ALL APPLICABLE HEALTH AND ENVIRONMENTAL
REGULATIONS.
ELIMINATE ALL SOURCES OF IGNITION. VENTILATE AREA.
VENTILATE AREA WITH EXPLOSION-PROOF EQUIPMENT. SPILLS MAY
BE COLLECTED WITH ABSORBENT MATERIALS. USE NON-SPARKING
TOOLS. EVACUATE ALL UNNECESSARY PERSONNEL.
COMPLETE PERSONAL PROTECTIVE EQUIPMENT MUST BE USED DURING
CLEANUP.

LARGE SPILLS - SHUT OFF LEAK IF SAFE TO DO SO. DIKE AND
CONTAIN SPILL. PUMP TO STORAGE OR SALVAGE VESSELS. USE
ABSORBENT TO PICK UP EXCESS RESIDUE. KEEP SALVAGEABLE
MATERIAL AND RINSE WATER OUT OF SEWERS AND WATER COURSES.
SMALL SPILLS - USE ABSORBENT TO PICK UP RESIDUE AND DISPOSE
OF PROPERLY.

SECTION 7 HANDLING AND STORAGE

HANDLING AND STORAGE

STORE BELOW 80F. KEEP AWAY FROM HEAT, SPARKS AND OPEN FLAME.

OTHER PRECAUTIONS

USE ONLY WITH ADEQUATE VENTILATION. DO NOT TAKE INTERNALLY.
KEEP OUT OF REACH OF CHILDREN. AVOID CONTACT WITH SKIN AND
EYES, AND BREATHING OF VAPORS. WASH HANDS THOROUGHLY AFTER
HANDLING, ESPECIALLY BEFORE EATING OR SMOKING.
KEEP CONTAINERS TIGHTLY CLOSED AND UPRIGHT WHEN NOT IN USE.
EMPTY CONTAINERS MAY CONTAIN HAZARDOUS RESIDUES.
GROUND EQUIPMENT WHEN TRANSFERRING TO PREVENT ACCUMULATION
OF STATIC CHARGE.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

COMMON NAME : ETHYLBENZENE

CAS NUMBER: 100-41-4

ACGIH(TWA): 100 PPM OSHA(TWA): 100 PPM

ACGIH(STEL): 125 PPM

COMMON NAME : MICA

CAS NUMBER: 12001-26-2

ACGIH(TWA): 3 MG/M3 OSHA(TWA): 3 MG/M3

COMMON NAME : XYLENE

CAS NUMBER: 1330-20-7

ACGIH(TWA): 100 PPM OSHA(TWA): 100 PPM

ACGIH(STEL): 150 PPM

COMMON NAME : TALC

CAS NUMBER: 14807-96-6

ACGIH(TWA): 2 MG/M3

COMMON NAME : N-BUTANOL

CAS NUMBER: 71-36-3

ACGIH(TWA): 20 PPM OSHA(TWA): 100 PPM

RESPIRATORY PROTECTION

CONTROL ENVIRONMENTAL CONCENTRATIONS BELOW APPLICABLE EXPOSURE STANDARDS WHEN USING THIS MATERIAL. WHEN RESPIRATORY PROTECTION IS DETERMINED TO BE NECESSARY, USE A NIOSH/MSHA (CANADIAN Z94.4) APPROVED ELASTOMERIC SEALING-SURFACE FACEPIECE RESPIRATOR OUTFITTED WITH ORGANIC VAPOR CARTRIDGES AND PAINT SPRAY (DUST/MIST) PREFILTERS. DETERMINE THE PROPER LEVEL OF PROTECTION BY CONDUCTING APPROPRIATE AIR MONITORING. CONSULT 29CFR1910.134 FOR SELECTION OF RESPIRATORS (CANADIAN Z94.4).

VENTILATION

PROVIDE DILUTION VENTILATION OR LOCAL EXHAUST TO PREVENT BUILD-UP OF VAPORS.
USE EXPLOSION-PROOF EQUIPMENT. USE NON-SPARKING EQUIPMENT.

PERSONAL PROTECTIVE EQUIPMENT

EYE WASH, SAFETY SHOWER, SAFETY GLASSES OR GOGGLES.
IMPERVIOUS GLOVES, IMPERVIOUS CLOTHING, FACE SHIELD, APRON, BOOTS.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

VAPOR PRESSURE:	NOT AVAILABLE	SPECIFIC GRAVITY:	1.355
BOILING RANGE (F/C):	243-290/117-143	WEIGHT PER GALLON:	11.29/ 13.56IMP
%VOLATILE BY VOLUME:	52.00		
PHYSICAL STATE:	LIQUID	APPEARANCE	WHITE
SOLUBILITY IN WATER:	NOT AVAILABLE	PH:	NOT AVAILABLE

SECTION 10: STABILITY AND REACTIVITY

UNDER NORMAL CONDITIONS

STABLE
SEE SECTION 5 FIRE FIGHTING MEASURES

MATERIALS TO AVOID

OXIDIZERS, ACIDS, BASES, ALDEHYDES, AMINES, NITRIC ACID, MINERAL ACIDS.

CONDITIONS TO AVOID

ELEVATED TEMPERATURES, CONTACT WITH OXIDIZING AGENT, STORAGE NEAR ACIDS, SPARKS, OPEN FLAME, IGNITION SOURCES.

HAZARDOUS POLYMERIZATION

WILL NOT OCCUR

SECTION 11: TOXICOLOGICAL INFORMATION

COMMON NAME :	RHEOLOGICAL ADDITIVE			
CAS NUMBER:	CONFIDENTIAL			
CARCINOGENICITY LISTED BY:	NTP NO	IARC NO	OSHA NO	ACGIH NO
COMMON NAME :	ETHYLBENZENE			
CAS NUMBER:	100-41-4			
CARCINOGENICITY LISTED BY:	NTP NO	IARC YES 2B	OSHA NO	ACGIH YES A3
LD50:	3500.00 MG/KG	ORL	RAT	
LD50:	2272.00 MG/KG	IPR	MOU	
LD50:	17.80 GM/KG	SKN	RBT	
COMMON NAME :	TRIETHYLENETETRAMINE			
CAS NUMBER:	112-24-3			
CARCINOGENICITY LISTED BY:	NTP NO	IARC NO	OSHA NO	ACGIH NO
LD50:	2500.00 MG/KG	ORL	RAT	
LD50:	1600.00 MG/KG	ORL	MOU	
LD50:	805.00 MG/KG	SKN	RBT	
COMMON NAME :	MICA			
CAS NUMBER:	12001-26-2			
CARCINOGENICITY LISTED BY:	NTP NO	IARC NO	OSHA NO	ACGIH NO
COMMON NAME :	ANTIGORITE			
CAS NUMBER:	12135-86-3			
CARCINOGENICITY LISTED BY:	NTP NO	IARC NO	OSHA NO	ACGIH NO
COMMON NAME :	XYLENE			
CAS NUMBER:	1330-20-7			
CARCINOGENICITY LISTED BY:	NTP NO	IARC NO	OSHA NO	ACGIH NO
LD50:	>1700.00 MG/KG	SKN	RBT	

2000.00590 221C0908 DEVTAR 5A CONVERTER

LD50: 4300.00 MG/KG ORL RAT
 LC50: 5000.00 PPM/4HR IHL RAT
 COMMON NAME : TREMOLITE
 CAS NUMBER: 14567-73-8
 CARCINOGENICITY LISTED BY: NTP NO IARC NO OSHA NO ACGIH NO
 COMMON NAME : TALC
 CAS NUMBER: 14807-96-6
 CARCINOGENICITY LISTED BY: NTP NO IARC NO OSHA NO ACGIH YES A4
 COMMON NAME : ANTHOPHYLLITE
 CAS NUMBER: 17068-78-9
 CARCINOGENICITY LISTED BY: NTP NO IARC NO OSHA NO ACGIH NO
 COMMON NAME : POLYAMIDE RESIN
 CAS NUMBER: 68410-23-1
 CARCINOGENICITY LISTED BY: NTP NO IARC NO OSHA NO ACGIH NO
 LD50:>5000.00 MG/KG SKN RAT
 LD50: 800.00 MG/KG ORL RBT
 LD50:>5000.00 MG/KG ORL RAT
 COMMON NAME : N-BUTANOL
 CAS NUMBER: 71-36-3
 CARCINOGENICITY LISTED BY: NTP NO IARC NO OSHA NO ACGIH NO
 LD50: 790.00 MG/KG ORL RAT
 LD50: 2680.00 MG/KG ORL MOU
 LD50: 3484.00 MG/KG ORL RBT
 LD50: 3400.00 MG/KG SKN RBT
 LC50: 8000.00 PPM/4HR IHL RAT
 COMMON NAME : CALCIUM ALKYL BENZENESULFONATE
 CAS NUMBER: 71486-79-8
 CARCINOGENICITY LISTED BY: NTP NO IARC NO OSHA NO ACGIH NO
 SUPPLEMENTAL HEALTH INFORMATION

CONTAINS A CHEMICAL THAT IS MODERATELY TOXIC BY INGESTION.
 CONTAINS A CHEMICAL THAT MAY BE ABSORBED THROUGH SKIN.
 NOTICE - REPORTS HAVE ASSOCIATED REPEATED AND PROLONGED
 OCCUPATIONAL OVEREXPOSURE TO SOLVENTS WITH PERMANENT BRAIN
 AND NERVOUS SYSTEM DAMAGE. INTENTIONAL MISUSE BY
 DELIBERATELY CONCENTRATING AND INHALING THE CONTENTS
 MAY BE HARMFUL OR FATAL.
 PROLONGED INHALATION OF MICA MAY CAUSE PNEUMOCONIOSIS.
 SYMPTOMS MAY INCLUDE A PROGRESSIVE DRY COUGH, SHORTNESS OF
 BREATH ON EXERTION, DECREASED CHEST EXPANSION, WEAKNESS AND
 WEIGHT LOSS.
 OTHER EFFECTS OF OVEREXPOSURE MAY INCLUDE TOXICITY TO LIVER,
 KIDNEY, CENTRAL NERVOUS SYSTEM, BLOOD.
 CARCINOGENICITY INHALATION OF NON-ASBESTIFORM COSMETIC GRADE TALC FOR
 2 YEARS AT 6 AND 18 MG/M3 PRODUCED CLEAR EVIDENCE OF
 CARCINOGENICITY IN FEMALE RATS (LUNG AND ADRENAL TUMORS) AND
 SOME EVIDENCE OF CARCINOGENICITY IN MALE RATS (ADRENAL
 TUMORS). NO EVIDENCE OF CARCINOGENICITY WAS DEMONSTRATED IN
 MALE AND FEMALE MICE EXPOSED UNDER THE SAME CONDITIONS.
 MICROSCOPIC EXAMINATION OF THE LUNGS OF RATS AND MICE
 EXPOSED TO TALC REVEALED ADDITIONAL EXPOSURE RELATED EFFECTS
 PRIMARILY ASSOCIATED WITH THE INFLAMMATORY RESPONSE.
 THE INTERNATIONAL AGENCY FOR RESEARCH ON CANCER (IARC) HAS
 EVALUATED ETHYLBENZENE AND CLASSIFIED IT AS A POSSIBLE HUMAN
 CARCINOGEN (GROUP 2B) BASED ON SUFFICIENT EVIDENCE FOR
 CARCINOGENICITY IN EXPERIMENTAL ANIMALS, BUT INADEQUATE
 EVIDENCE FOR CANCER IN EXPOSED HUMANS.
 IN A 2 YEAR INHALATION STUDY CONDUCTED BY THE NATIONAL
 TOXICOLOGY PROGRAM (NTP), ETHYLBENZENE VAPOR AT 750 PPM
 PRODUCED KIDNEY AND TESTICULAR TUMORS IN RATS AND LUNG
 AND LIVER TUMORS IN MICE. GENETIC TOXICITY STUDIES
 SHOWED NO GENOTOXIC EFFECTS. THE RELEVANCE OF THESE
 RESULTS TO HUMANS IS NOT KNOWN.

REPRODUCTIVE EFFECTS

HIGH EXPOSURES TO XYLENE IN SOME ANIMAL STUDIES, OFTEN AT MATERNALLY TOXIC LEVELS, HAVE AFFECTED EMBRYO/FETAL DEVELOPMENT. THE SIGNIFICANCE OF THIS FINDING TO HUMANS IS NOT KNOWN.

MUTAGENICITY NO MUTAGENIC EFFECTS ARE ANTICIPATED
 TERATOGENICITY NO TERATOGENIC EFFECTS ARE ANTICIPATED

SECTION 12: ECOLOGICAL INFORMATION

NO ECOLOGICAL TESTING HAS BEEN DONE BY ICI PAINTS ON THIS PRODUCT AS A WHOLE.

SECTION 13: DISPOSAL CONSIDERATIONS

WASTE DISPOSAL DISPOSE IN ACCORDANCE WITH ALL APPLICABLE REGULATIONS.
 AVOID DISCHARGE TO NATURAL WATERS.

SECTION 14: TRANSPORT INFORMATION

DOT UN1263, PAINT, 3, PGIII
 IMDG UN1263, PAINT, CLASS 3, PGIII, LTD QTY (IMDG 3.4.7)
 UN1263, PAINT, CLASS 3, PGIII
 IATA UN1263, PAINT, 3, PGIII
 TDG NOT AVAILABLE

SECTION 15: REGULATORY INFORMATION

	SARA	SARA	CERCLA	HAZ AIR	MARINE
	302	313	302.4	POLLUTANT	POLTNT
CAS NUMBER: 100-41-4	NO	YES	YES	YES	NO
COMMON NAME : ETHYLBENZENE					
CAS NUMBER: 1330-20-7	NO	YES	YES	YES	NO
COMMON NAME : XYLENE					
CAS NUMBER: 71-36-3	NO	YES	YES	NO	NO
COMMON NAME : N-BUTANOL					

AS OF THE DATE OF THIS MSDS, ALL OF THE COMPONENTS IN THIS PRODUCT ARE LISTED (OR ARE OTHERWISE EXEMPT FROM LISTING) ON THE TSCA INVENTORY.

THIS PRODUCT HAS BEEN CLASSIFIED IN ACCORDANCE WITH THE HAZARD CRITERIA OF THE CPR (CONTROLLED PRODUCTS REGULATIONS) AND THE MSDS CONTAINS ALL THE INFORMATION REQUIRED BY THE CPR.

SECTION 16: OTHER INFORMATION

THE INFORMATION CONTAINED HEREIN IS BASED ON DATA AVAILABLE AT THE TIME OF PREPARATION OF THIS DATA SHEET AND WHICH ICI PAINTS BELIEVES TO BE RELIABLE. HOWEVER, NO WARRANTY IS EXPRESSED OR IMPLIED REGARDING THE ACCURACY OF THIS DATA. ICI PAINTS SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS INFORMATION, OR OF ANY PRODUCT, METHOD OR APPARATUS MENTIONED AND YOU MUST MAKE YOUR OWN DETERMINATION OF ITS SUITABILITY AND COMPLETENESS FOR YOUR OWN USE, FOR THE PROTECTION OF THE ENVIRONMENT, AND THE HEALTH AND SAFETY OF YOUR EMPLOYEES AND USERS OF THIS MATERIAL.
 COMPLIES WITH OSHA HAZARD COMMUNICATION STANDARD 29CFR1910.1200.